



DVR



DMR-403C / DMR-403CP

4-Ch. M-JPEG Mobile DVR

Features

- MJPEG Compression
- Up to 30fps Recording Speed
- 4Ch Motion Detection
- 4ch Alarm Sensor (reverse , left turning signal, right turning signal, other)
- Search Data by Time / Date , Events List
- Audio Recording
- Support SATA*1 HDD (Max.500G)
- Optional with Heater & Bracket

Specification

Model		DMR-403C / DMR-403CP
Video	Input	4CH Composite
	Output	2CH Composite
Monitoring	Display Frame	NTSC:120 fps (4x30 fps) ; PAL:100 fps (4x25 fps)
	Resolution	NTSC: 720(H) X 480(V) / PAL: 720(H) X 576(V)
Record / Playback	Recording Resolution	NTSC: 640(H) X 224(V) / PAL: 640(H) X 272(V)
	Recording Frame Rate(Quad)	Max. NTSC:30 fps / PAL:25 fps
	Recording Frame Rate(Each)	Max. NTSC:7.5 fps (30 fps / 4) ; PAL:6.25 fps (25 fps / 4)
	Storage Capacity	SATA*1 Max 500G
	Compression	Advanced MJPEG Low:12K Bytes / Frame Normal:15K Bytes / Frame High:20K Bytes / Frame
	Record Mode	Continuous / Motion / Programmed
	Search Mode	time / date , events list
	Motion detect	4ch motion detect
Audio	Audio Recording And playing	1ch audio input/output Real time recording and playing
	Video Loss display	Yes
	Auto ch_switching	Yes
	Buzzer output mode	v_loss,motion,sensor
	Imaging adjust	Light,contrast,color
	Other video input	4ch camera composite for DC12V max:0.5A
	Alarm sensor input	4ch sensor (reverse , left turning signal, right turning signal, other)
Mechanics	Operation Temperature	0~50°C ; Heater:-30°C~65°C ; -30°C col_storage to start 10~20min
	Operating vibration	0.5G (10 ~ 500Hz)
	Dimension	440(W)x412.2(D)x88(H)mm
	Power Supply	DC 8 ~ 28V (MAX:36V) about 15W add HD + heater 50W



Application Guide

